

SPIROL®

SPECIAL COILED SPRING PINS

SPIROL® SERIES 500 EXTRA LIGHT DUTY PINS

These pins were specifically designed for use in soft or fragile materials. The 1½ coil formation ensures that the radial force exerted against the hole wall does not exceed the strength of the hole material to prevent deformation. These pins are also an economical solution where pin strength is not a major design consideration. Typical applications for Series 500 Pins include: hinge pins in plastic or ceramic assemblies, alignment pins, and fastening applications where the hole is close to an edge of an assembly component.



MATERIAL


B High Carbon Steel
C Chrome Stainless Steel
D Nickel Stainless Steel

FINISHES

K Plain, oiled
P Passivated, oiled
T Zinc Plated

PIN DUTIES

XL Extra Light



DIMENSIONAL DATA — METRIC

NOMINAL PIN SIZE	PIN DIAMETER D		CHAMFER		RECOMMENDED HOLE SIZE		DOUBLE SHEAR STRENGTH kN MIN.		LENGTHS
			B	C					L
	MAX.	MIN.	DIA.	LENGTH	MAX.	MIN.	HIGH CARBON / CHROME STAINLESS STEEL	NICKEL STAINLESS STEEL	TOLERANCE ± .050
2.5	2.87	2.65	2.4	0.7	2.6	2.49	1	0.75	10 to 24
3	3.4	3.15	2.9	0.9	3.1	2.99	1.5	1.15	12 to 30
4	4.5	4.2	3.9	1.1	4.12	3.98	2.8	2.1	16 to 40
5	5.57	5.25	4.85	1.3	5.12	4.95	4	3	20 to 45
6	6.72	6.25	5.85	1.5	6.13	5.95	6	4.6	24 to 50

DIMENSIONAL DATA — INCH

NOMINAL PIN SIZE	PIN DIAMETER D		CHAMFER		RECOMMENDED HOLE SIZE		DOUBLE SHEAR STRENGTH LBS. MIN.		LENGTHS
			B	C					L
	MAX.	MIN.	DIA.	LENGTH	MAX.	MIN.	HIGH CARBON / CHROME STAINLESS STEEL	NICKEL STAINLESS STEEL	TOLERANCE ± .010
.094 3/32	.108	.099	.091	.038	.097	.093	225	175	.375 to 1.000
.125 1/8	.141	.131	.121	.044	.129	.124	400	300	.500 to 1.250
.156 5/32	.174	.163	.152	.048	.160	.155	620	480	.625 to 1.750
.187 3/16	.210	.196	.182	.055	.192	.186	900	700	.750 to 1.750
.250 1/4	.276	.260	.243	.065	.256	.247	1600	1200	1.000 to 2.000

Specifications on other metric and inch diameters and lengths are available on request.

All special Coiled Pins are subject to minimum order quantities.





**Innovative Fastening Solutions.
Lower Assembly Costs.**



Coiled Spring Pins




Slotted Spring Pins




Solid Pins



**Alignment Dowels /
Bushings**



**Spacers & Rolled
Tubular Components**



**Compression
Limiters**



**Threaded Inserts
for Plastics**



Disc Springs



**Machined Aerospace
Components**



**Precision Shims,
Washers & Metal Gaskets**



Laminated Shims



**Parts Feeding
Technology**



**Pin Installation
Technology**



**Insert Installation
Technology**



**Compression Limiter
Installation Technology**

Please refer to www.SPIROL.ca for current specifications and standard product offerings.

SPIROL offers complimentary Application Engineering support! We will assist on new designs as well as help resolve issues, and recommend cost savings on existing designs. Let us help by visiting **Application Engineering Services** on SPIROL.ca.

Technical Centres

Americas **SPIROL Canada**
Windsor, Ontario
+1 519 974 3334
info-ca@spirol.com

SPIROL International Corporation
Connecticut, USA
+1 860 774 8571
info@spirol.com

SPIROL Shim Division
Ohio, USA
+1 330 920 3655
info@spirol.com

SPIROL Mexico
Apodaca, Nuevo León
+52 81 8385 4390
info-mx@spirol.com

SPIROL Brazil
Indaiatuba, São Paulo
+55 19 3936 2701
info-br@spirol.com

Europe **SPIROL United Kingdom**
Corby, Northants, England
+44 (0) 1536 444800
info-uk@spirol.com

SPIROL Ford
South Shields, Tyne & Wear, England
+44 (0) 1914 540141
contactus@ford-engineering.com

SPIROL France
Saint-Léonard
+33 (0) 3 26 36 31 42
info-fr@spirol.com

SPIROL Germany
Münich
+49 (0) 89 4 111 905 71
info-de@spirol.com

SPIROL Spain
Barcelona
+34 932 71 64 28
info-es@spirol.com

SPIROL Czech Republic
Tuchoměřice
+420 226 218 935
info-cz@spirol.com

SPIROL Poland
Warsaw
+48 510 039 345
info-pl@spirol.com

Asia Pacific **SPIROL China**
Shanghai
+86 (0) 21 5046-1451
info-cn@spirol.com

SPIROL Malaysia
Iskandar Puteri, Johor
+60 77 063 960
info-my@spirol.com

SPIROL Korea
Seoul, South Korea
+82 (0) 10 9429 1451
info-kr@spirol.com